

3/19/1

DIALOG(R)File 347:JAPIO

(c) 2002 JPO & JAPIO. All rts. reserv.

03758022 \*\*Image available\*\*

INPUT DEVICE

PUB. NO.: 04-123122 [ JP 4123122 A]

PUBLISHED: April 23, 1992 (19920423)

INVENTOR(s): KASHII MASAHARU

APPLICANT(s): SONY CORP [000218] (A Japanese Company or Corporation), JP  
(Japan)

APPL. NO.: 02-243467 [JP 90243467]

FILED: September 13, 1990 (19900913)

INTL CLASS: [5] G06F-003/033; G06K-011/18

JAPIO CLASS: 45.3 (INFORMATION PROCESSING -- Input Output Units)

JAPIO KEYWORD: R098 (ELECTRONIC MATERIALS -- Charge Transfer Elements, CCD &  
BBD); R116 (ELECTRONIC MATERIALS -- Light Emitting Diodes,  
LED); R131 (INFORMATION PROCESSING -- Microcomputers &  
Microprocessors)

JOURNAL: Section: P, Section No. 1403, Vol. 16, No. 382, Pg. 84,  
August 14, 1992 (19920814)

#### ABSTRACT

PURPOSE: To three-dimensionally execute the detection and to enlarge the degree of freedom of operation by providing an index member which a moving body to be inspected has, a detecting means for detecting the index member, and a display means for displaying an index member position detected from the detecting means, and displaying plural index member positions as a cursor on the display means.

CONSTITUTION: Sensors 13a, 13b catch and detect plural pointing devices 12 being for instance, handled by a person or had on his finger, or are attached to his clothes of a moving body 11 to be inspected who is looking at the screen of a CRT 5 in front of a display means 22, together with a person's motion, and display a position of the pointing device 12 as a cursor 30 on the screen of the CRT 5. That is, by a fact that a person moves the pointing device 12, while looking at a cursor position, it is utilized as the cursor 30 such as a sound is generated simultaneously, etc. In such a way, the operation range is enlarged, and that which has a large degree of freedom of operation can be obtained.